THE POSSIBILITIES ARE INFINITE FUJITSU

DATA SHEET

A19-3

Issue: **May 2009**

All-round Display

A Line TFT 48cm/19- inch display – Enter the world of LCD

The A19-3 offers you all the benefits of LCD technology at a very competitive price.

Excellent visual ergonomics for the office with 1280 x 1024 recommended resolution, 800:1 typical contrast and excellent brightness of 300 cd/m²

Fast response time (typ.) of 5 ms, perfect for Internet, office multitasking and more

Proven ECO friendliness with TCO'03 and Energy Star

Representative design providing a slender housing in ergonomic light grey, integrated speakers and power supply

ENERGY STAR

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

Works with Windows Vista®

5ms RESPONSE TIME

SPEAKER

A19-3

Ergonomic stand	
Tilt angle	-5° / + 20°
Picture performance	
Contrast - typical	800:1
Response time typical	5 ms
Viewing angle (h/v)	170° / 170°
Brightness - typical	300 cd/m2
Size and resolution	
Aspect ratio	5:4
Diagonal Size	48 cm / 19-inch
Resolution (native)	1280 x 1024 pixel (recommended)
Resolution (interpolated)	1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	376 x 301 mm
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	55 - 75 Hz
Connectivity	
Video input	1 x D-SUB
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack
Ease-of-use menu	
Languages	Dutch, English, French, German, Italian, Russian, Spanish, Swedish
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	sRGB, 6500K, 9300K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode
Setup	Language, DDC-CI, OSD-Position, OSD-Timeout, Factory recall
Power consumption	
Soft switch off	0.7 W
Power save mode	0.8 W
Operating with EPA settings	23 W
Operating maximum brightness	35 W
Electrical values	
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1
Compliance	
Germany	GS
Europe	CE
USA/Canada	FCC Class B, cUL
Russia	GOST
China	CCC
Saudi Arabia	SASO
Global	TCO'03, ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability

MTBF (demonstrated)	70000 h

Dimensions / Weight / Environmental

Dimension without stand (W x D x H)	412 x 62 x 350
Dimension with stand (W x D x H)	412 x 200 x 402
Weight (packed)	6.3
Weight (unpacked)	4.3 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous

	Kensington lock prepared

Package content

	D-SUB Data cable 1.8m , Audio cable , Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, Quickstart flyer, Warranty booklet, Safety booklet
	Data cables and audio cable detachable on display

Order information

Order Code	S26361-K1147-V140
EAN-Nr.	4049699076411

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions May 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com